

IN THE CLAIMS:

Claim 1 (Original): A method of fabricating a liquid crystal display device,
comprising the steps of:

forming a gate electrode, a gate bus line, and a gate pad on a substrate using a
first mask process;

forming a gate insulating layer and an active layer on an entire surface of the
substrate;

forming a first organic material film on an entire surface of the substrate;

moving a portion of the first organic material film to expose a first portion of
the gate pad;

depositing a transparent film on an entire surface of the substrate;

patterning the transparent film using a second half-tone mask to form a data
bus line, a source electrode, a drain electrode, a pixel electrode, a channel layer, and
an ohmic contact layer;

exposing portions of the data pad and data bus line using a third mask;

forming a second organic material film on an entire surface of the substrate;

depositing a low resistance material on the data bus line;

coating a passivation film on the substrate;

removing the second organic material film using a lift-off process to expose a
second portion of the gate pad and a first portions of the data pad.

Claim 2 (Original): The method according to claim 1, wherein the pixel electrode, the source electrode, the drain electrode, and the data bus line are simultaneously formed on the active layer.

Claim 3 (Original): The method according to claim 1, wherein the transparent electrode material includes indium tin oxide.

Claim 4 (Original): The method according to claim 1, wherein the low resistance material includes at least one of Cu, Ag, Au, Ti, and W.

Claim 5 (Original): The method according to claim 1, wherein the step of depositing a low resistance material includes one of an electrical plating method and an electroless plating method.

Claim 6 (Original): The method according to claim 1, wherein the step of removing a portion of the first organic material film includes an etching process.

Claim 7 (Currently Amended): A method of fabricating a liquid crystal display device, comprising the steps of:

forming a gate electrode, a gate bus line, and a gate pad on a substrate;

forming a gate insulating layer, an active layer, and a transparent conductive film on an entire surface of the substrate;

patterning the active layer and the transparent conductive film to concurrently form a data bus line, a data pad, a source electrode, a drain electrode, a pixel electrode, a channel layer, and an ohmic contact layer;

forming an organic material film on the gate and data pads;

forming a passivation layer on an entire surface of the substrate including the organic material film; and

exposing portions of the gate and data pads,

wherein the data bus line, and the source, drain, and pixel electrodes include the transparent conductive film.

Claim 8 (Original): The method according to claim 7, wherein the step of patterning the active layer and the transparent conductive film includes a half-tone mask.

Claim 9 (Original): The method according to claim 7, wherein the transparent conductive film includes indium tin oxide.

Claim 10 (Canceled).

Claim 11 (Currently Amended): The method according to claim ~~10~~ 7, wherein the step of exposing the gate and data pads includes removing the organic material film using a lift-off method.

Claim 12 (Original): The method according to claim 7, further comprising a step of forming a low resistance metal on the source electrode before the step of exposing the gate and data pads.

Claim 13 (Original): The method according to claim 12, wherein the low resistance metal includes at least one of Cu, Ag, Au, Ti, and W.

Claim 14 (Withdrawn): A liquid crystal display device, comprising:

- a gate electrode, a gate bus line, and a gate pad on a substrate;

- a data bus line and data pad on the substrate;

- a gate insulating layer an entire surface of the substrate;

- an active layer on a portion of the gate insulating layer;

- a source electrode, a drain electrode, and a pixel electrode on the active layer;

and

- a low resistance material on the data bus line,

wherein the data bus line, the gate and data pads, the source and drain electrodes, and the pixel electrode are formed of transparent conductive material.

Claim 15 (Withdrawn): The device according to claim 14, further comprising an auxiliary capacitor including the gate bus line, the gate insulating film, the active layer, and the transparent conductive material.

Claim 16 (Withdrawn): The device according to claim 14, wherein drain and pixel electrodes are integrally formed along a direction of the gate line.

Claim 17 (Withdrawn): A liquid crystal display device, comprising:

- a gate bus line on a substrate;

- a gate insulating layer formed on the gate bus line;

- an active layer formed on the gate insulating layer; and

- an auxiliary capacitor electrode including indium tin oxide film formed exclusively on the active layer.

Claim 18 (Withdrawn): The device according to claim 17, further comprising a data bus line on the substrate.

Claim 19 (Withdrawn): The device according to claim 18, wherein the data bus line includes the indium tin oxide film.

Claim 20 (NEW): The method according to claim 7, wherein the organic material film is formed by a printing method.